

Kapiro S4 Airkos

- 4 arc sensors**
- DIN 9 to DIN 13 variable shade**
- Grinding mode**
- Side vision**
- Particules filtration (PRSL)**
- 2 airflows**
- Clogged-filter alarm**
- Low-battery alarm**
- Storage bag**



La technique

Welding shade	Variable DIN 9 to DIN 13	Belt	Large and padded Neoprene
LC technology	Twisted Nematic	Spark protection	Indirect filter cover
Optical Classes	1/1/1/2	Hose cover	Included - Flame retardant
Sensitivity setting	Stepless	Sound level	60dB
Power	Solar	Headgear	Confort - 4 settings
Delay setting	From 0,1s to 1s	Airflow	180l/m and 220l/m
Grinding	Yes - Blocked shade DIN 4	Operating time	9-10 hours
Applications	Electrodes, MIG/MAG, TIG	Sound alarm	Low battery charge
Standards	EN12941	Belt adjustment	Double fast setting - No velcro
Outside protection	Clear polycarbonate	Arc sensors	4 - Independent
Filtration	TH2PSL	Switching speed	0,2ms
Sound alarm	Clogged filter	Viewing area	93 x 43mm
Battery	Lithium-Ion - Removable	Weight	1180g (unité+batterie+ceinture+filtre)
Charger	6 hours smart charge (for CR7020)	Side vision	Shade DIN 5 polycarbonate