

## FLANGE FACING ATTACHMENT

■ The flange facing attachment has been designed to be quickly adapted on any standard pipe bevelling machine of our range, to further multiply its use by also allowing it to resurface all the different flanges welded on pipes, directly on site,

■ Therefore we have a portable inner clamping flange facing machine to perform any geometry required by the customer; by just bringing the tool to the flange on site, where most needed.

■ One skilled operator will adapt it on our machines in a matter of minutes. Its clutch, dual side machining and different feeds will allow the operator to face damaged flanges to their original shape and with different finishes.



US150ASB

■ It may be used by clamping the machine directly inside the pipe, or if an extreme squareness and centering is required, the spider shaped elbow mandrel kit will be necessary.



US25ACC

## DIMENSIONS

Machine	Minimum	Maximum	Inches
US25ACC	25 mm	300 mm	1" • 12"
US30ASB	50 mm	355 mm	2" • 14"
US40ASB	70 mm	400 mm	2"1/2 • 16"
US80ASB	100 mm	610 mm	4" • 24"
US150ASB	165 mm	900 mm	6"1-2 • 36"

## OPTIONS

■ The machines have to be hydraulic driven with a 4 kW or 5.5 kW Protem power pack ( version from US40ASB).



US40ASB