

## HYDRAULIC POWER PACKS BELUGA and HPP 050

■ These hydraulic power packs have been specially designed for PROTEM (for the US and TTNG machine series).

■ They are equipped with an electric remote control, and a powerful air cooling system.

■ They have a fixed flow rate.

A pressure gauge enables clear visualisation of the pressure and they are fitted with a rotation direction inverter.

■ Their dimensions make them easy to transport and being user-friendly and rapid, they are intended for multiple uses on diverse sites.

■ They are supplied with flexible hoses equipped with non-spill type flush faced Quick Disconnect couplings.



### TECHNICAL SPECIFICATIONS

Model	BELUGA	HPP 050
Power	3 KW Direct start up	5,5 KW single pump Direct start up
Voltage	400 V 50/60 Hz	400 V 50 Hz
Circuit Rotation	Fixed Flow Rate : 29 L/min	Fixed Flow Rate : 33 L/min Dual Rotation Direction
Pressure	Max : 100 Bars	Max : 90 Bars
Hoses	Length : 3 metres	Length : 5 metres
Weight	65 kg	140 kg
Packaging	Wooden case	Wooden case
Oil volume	3 L	45 L
Oil Type	ISO VG46	S46HV ISO VG46
Options	- Hot weather - Cold weather	- 15 m of flexible hoses - Oil sump - Remote control - Others : please consult us.

### DIMENSIONS

HPP 050

